

DURAGUARD™

TECHNOLOGY TO BREAK THE SAFETY BARRIER



FEATURES

- Continuous constant support at the face
- Operator drills from a protected position
- Load indicator for quick support monitoring
- Can be integrated with blasting barricades, netting and rock drills
- Simple to install and maintain

DESIGN SPECIFICATIONS

| Item | Parameter | Value |
|------|-------------------------------------|-----------------------|
| 1 | Stoping width | 600mm to 1600mm* |
| 2 | Rockfall protection for operator | Constant** |
| 3 | Preload force | 50 kN per leg |
| 4 | Step advance | 300mm per step |
| 5 | Blast on capacity | Integrated barricades |
| 6 | Steerability | Yes |
| 7 | Rockburst control | Yes |
| 8 | Max. footwall & hanging wall stress | 30 MPa |
| 9 | Max. mass | 25 kg per component |
| 10 | Maintenance | Basic tools only |

* Cylinder length dependent

** Provided units are linked with netting

SABS
ISO 9001

HEAD OFFICE
670 Power Road,
Industries West
Germiston, 1450
South Africa

Tel +27 (0) 11 876 5040
Fax +27 (0) 11 873 3532

SALES OFFICE
30 van der Bijl Street,
Westonaria,
1780
South Africa

Tel +27 (0) 11 411 4500
Fax +27 (0) 11 411 4507

www.duraset.com


DURASET

THE AVENG GROUP